

**AMENDMENTS TO THE CLAIMS**

1. (Currently Amended) Ear protector arranged to protect a first ear and a second ear from loud noise, comprising a bow which has a first part connecting a second part and a third part, said second part comprising at least a first contact point to be applied in proximity to said first ear, said third part comprising at least a first contact point to be applied in proximity to said second ear, characterized in that the ear protector comprises a fourth part arranged rotatably on said second part and comprising a first ear plug which fits into said first ear to suppress noise, the ear protector comprises a fifth part arranged rotatably on said third part and comprising a second ear plug which fits into said second ear to suppress noise, said fourth part is designed to be able to assume a first position in which said ear plug is in a position outside said first ear, and a second position in which said ear plug is in a position which fits in said ear in order thereby to suppress noise, said fifth part is designed to be able to assume a first position in which said ear plug is in a position outside said ~~auditory canal~~ second ear, and a second position in which said ear plug is in a position in said ~~auditory canal~~ second ear in order thereby to suppress noise;  
said fourth and fifth parts are pretensioned by a spring so that, in said second position, they exert a pressure inwards towards said auditory canal.

2. (Original) Ear protector according to claim 1, in which said fourth and fifth parts fit into a respective auditory canal of the respective said ear.

3. (Original) protector according to claim 1, in which said second and third parts are arranged to pass round the pinna of an ear and in this way hold said ear protector securely in a position such that

said fourth and fifth parts, in the respective second position, fit said ear plugs into said auditory canals.

4. (Original) Ear protector according to claim 1, in which said first part is pretensioned by a spring so that said second and third parts press towards a position in proximity to said ears in order to hold said ear protector securely in a position such that said fourth and fifth parts, in the respective second position, fit said ear plugs into said auditory canals.

5. (Cancelled)

6. (Original) Ear protector according to claim 1, in which said fourth and fifth parts are pretensioned by a spring in said second position so as to assume said first position under a slight pressure.

7. (Original) Ear protector according to claim 1, in which said ear protector comprises a radio, mobile telephone, pager or other electronic equipment and devices for conveying sound or a signal in an audible manner through said ear plugs.

8. (Original) Ear protector according to claim 1, in which said ear plugs can be exchanged from said fourth and fifth parts.